



TOUCH-UP PAINT 1C

PAINTING - TOUCH-UP

- 1 Component acrylic spray paint in can.
- Suitable for painting, repairing, or repainting of powdercoated objects.
- Application: standard painting and repairs.
- Direct adhesion on PVC and powder paint, after suitable preparation!
- Pre-treatment with the Duthoo Epoxy Primer or Universal Primer on steel, galva, stainless steel, aluminium and non-ferrous, after suitable preparation of the substrate.
- Yield: 8 à 10 m² per litre for 25/30 µ dry film thickness.
- Available in all RAL-colors(matt 30%, semi-gloss 70% and high-gloss 85%), transparant and all PVC -& powdercoat colors.
- Shelf life: 1 year in unopened packaging - keep away from frost, humidity and warmth.
- Quick drying
- Does not turn yellow
- Strong coverage power

MIXING RATIO

- **PART A:** Touch-Up Paint 1C on gloss
PART B: PU Thinner
POTLIFE: unlimited

	PART A	PART B
Ratio in volume	100	50/60

PREPARATION

- The surfaces must be free of any impurities.
Sanding with Duthoo Abranylon and degreasing of non-ferrous metals with the Etching Promotor.
- Apply primer and paint with the color of choice.
- Sanding and applying primer on powdercoated surfaces and PVC is not necessary after degreasing with the Etching Promotor and afterwards a waiting time before painting of at least 15 min and within 3h.
Mix paint and thinner well !

APPLY METHOD

- **Spragun:**
Nozzle: 1,4mm. Apply in 2 layers.
Metallic tints can require an extra varnish layer.
- **Drying:**
For a dry layer thickness: 30µ - air temperature of 20°C - Relative humidity 60% :
Dust dry: 10min / Manageable: 30min / Completely dry: 2h

PACKAGING

1L - 3L - 5L - 12,5L - 25L