

Technical Data Sheet



SPRAYMASTIC FILLER

- Sprayable filler for quick filling and leveling of unevennesses and scratches on powdercoated metals and on old hardened paints.
- Color: light grey.

TECHNICAL PROPERTIES

- Fast drying and good abrasion.
- Direct adhesion on aluminium, non-ferrous and paints.
- Application temperature: between 18 to 20 °.
- Professional use.
- Fast dust dry / Overcoatable with the Touch Up Spray after 2 hours (test in advance)
- Product, which is dry to the core, can be painted with powder paint.
- Shelf life: 1 year in unopened packaging. Store according to the general requirements for aerosols. Keep away from frost, humidity and heat.
- Flammable

USE

- The surfaces must be free of any impurities.
After the appropriate preparation of the substrate that needs to be filled (sand with Duthoo Abranylon, sand with P240, sandblasting, pickling,enz.), degrease and clean with the Etching Promotor.
- Shake spraycan well before use (2 to 3 minutes). Spray at a distance of 10-15 cm.
Apply in several coats untill the unevenness is filled.
- After complete drying, sand with P240 to full equalization of surface. And finally sand with P320, before painting. If necessary repeat the action until the desired result.
- The spraycan contains 1 nozzle: 1 round jet.
- Avoid use at temperature below 15 ° c and in extreme heat or humidity.
- To promote the retention time of your spraycan, hold your spraycan upside down and spray until no more paint comes out. Store upside down.

PACKAGING

400 ML SPRAY CAN