

Duthoo Touch-Up Spray 1 Component

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 - Product identifier

Trade name/designation Duthoo Touch-Up Spray 1 Component
Chemical name Duthoo Touch-Up Spray 1C
Product-type Mixture
UFI: VM00-P0CV-A00E-F3E7

1.2 - Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses - Coatings and paints, thinners, paint removers
- For professional use only

1.3 - Details of the supplier of the safety data sheet

-Duthoo Coating Concepts
Pluim 1
8550 Zwevegem Belgium
Telephone : 0032 56 360774 Fax 0032 56 694760
Website www.duthoo.eu
Eddy Crepeele: 0032 56 360774/0032 471 410802 eddy@duthoo.eu

1.4 - Emergency telephone number

- Poison Centre. Tel: (+32) 070 245 245 or (+32) 02 264 96 30 Belgium

SECTION 2: Hazards identification

2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2	Eye irritation - Category 2
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)
Aerosol 1	Aerosol - Category 1

2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: acetone, propan-2-one, propanone (CAS No.: 67-64-1) | n-butyl acetate (CAS No.: 123-86-4) | ethyl acetate (CAS No.: 141-78-6)

Signal word : Danger

Hazard pictograms



Hazard statements

H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Precautionary statements

Duthoo Touch-Up Spray 1 Component

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P280	Wear protective gloves/protective clothing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to an appropriate recycling or disposal facility in accordance with national regulation.

EUH-phrases

EUH066	Repeated exposure may cause skin dryness or cracking
EUH205	Contains epoxy constituents. May produce an allergic reaction
EUH208	Contains n-butyl methacrylate (97-88-1) . May produce an allergic reaction

2.3 - Other hazards

SECTION 3: Composition / information on ingredients

3.1 - Substances

Not applicable

3.2 - Mixtures

Chemical name	No	%	Class(es)	Specific concentration limit
Dimethyl ether	CAS No. : 115-10-6 Index No. : 603-019-00-8 EC No. : 204-065-8	> 50 - < 75	Flam. Gas 1 - H220 Press. Gas Press. Gas (Liq.) - H280	Not applicable
acetone, propan-2-one, propanone	CAS No. : 67-64-1 Index No. : 606-001-00-8 EC No. : 200-662-2	> 15 - < 30	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
n-butyl acetate	CAS No. : 123-86-4 Index No. : 607-025-00-1 EC No. : 204-658-1	> 5 - < 15	Flam. Liq. 3 - H226 STOT SE 3 (H336) - H336	Not applicable
reaction mass of ethylbenzene and xylene	CAS No. : Index No. : EC No. : 905-588-0 REACH No. : 01-2119539452-40	> 1 - < 5	Acute Tox. 4 Dermal - H312 Acute Tox. 4 Inhalation - H332 Aquatic Chronic 3 - H412 Asp. Tox. 1 - H304 Eye Irrit. 2 - H319 Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 STOT RE 2 - H373 STOT SE 3 (H335) - H335	ATE dermal 1100 ATE Inhalation Vapor 11
ethyl acetate	CAS No. : 141-78-6 Index No. : 607-022-00-5 EC No. : 205-500-4	> 1 - < 5	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
n-butyl methacrylate	CAS No. : 97-88-1 Index No. : 607-033-00-5 EC No. : 202-615-1	> 0,1 - < 1	Eye Irrit. 2 - H319 Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 (H335) - H335	Not applicable

SECTION 4: First aid measures

4.1 - Description of first aid measures

Duthoo Touch-Up Spray 1 Component

<u>Following inhalation</u>	- Provide fresh air.
<u>Following skin contact</u>	- When in doubt or if symptoms are observed, get medical advice.
<u>After eye contact</u>	- Rinse immediately carefully and thoroughly with eye-bath or water. - In case of eye irritation consult an ophthalmologist.

4.2 - Most important symptoms and effects, both acute and delayed

<u>Symptoms and effects - Following inhalation</u>	- No information available.
<u>Symptoms and effects - Following skin contact</u>	- No information available.
<u>Symptoms and effects - After eye contact</u>	- Causes eye irritation.

4.3 - Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 - Extinguishing media

<u>Suitable extinguishing media</u>	- ABC-powder - Carbon dioxide (CO ₂) - Foam - Extinguishing powder
<u>Unsuitable extinguishing media</u>	- Full water jet

5.2 - Special hazards arising from the substance or mixture

<u>Special hazards arising from the substance or mixture</u>	- Hazardous combustion products - Pressurised container: May burst if heated.
<u>Hazardous decomposition products</u>	- Carbon dioxide (CO ₂) - Carbon monoxide - Nitrogen oxides (NO _x)

5.3 - Advice for firefighters

- Wear a self-contained breathing apparatus and chemical protective clothing.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1 - Personal precautions, protective equipment and emergency procedures

<u>For non-emergency personnel</u>	- Use personal protection equipment. - Provide adequate ventilation. - Remove all sources of ignition. - Wear breathing apparatus if exposed to vapours/dusts/aerosols.
<u>For emergency responders</u>	- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Duthoo Touch-Up Spray 1 Component

6.2 - Environmental precautions

- Do not allow to enter into surface water or drains.

6.3 - Methods and material for containment and cleaning up

Methods and material for containment - Soak up inert absorbent and dispose as waste requiring special attention.

Methods and material for cleaning up - Ventilate affected area.
- Take up mechanically, placing in appropriate containers for disposal.

Inappropriate techniques - No information available.

6.4 - Reference to other sections

- Disposal: see section 13
- Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1 - Precautions for safe handling

Recommendation - Avoid: Eye contact
- It is recommended to design all work processes always so that the following is excluded: generation/formation of aerosols
- Vapours can form explosive mixtures with air.
- When using do not smoke.
- Use only in well-ventilated areas.
- Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advices on general occupational hygiene - Avoid contact with skin, eyes and clothes.
- Wash hands before breaks and after work.

7.2 - Conditions for safe storage, including any incompatibilities

- Keep container tightly closed and in a well-ventilated place.
- Do not store together with: Combustible substance
- Protect against: Heat
- Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

7.3 - Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 - Control parameters

acetone, propan-2-one, propanone (67-64-1)	
IOELV TWA mg/m ³ (UE)	1210 mg/m ³
IOELV TWA ppm (UE)	500 ppm
Dimethyl ether (115-10-6)	
IOELV TWA mg/m ³ (UE)	1920 mg/m ³
IOELV TWA ppm (UE)	1000 ppm

Duthoo Touch-Up Spray 1 Component

n-butyl acetate (123-86-4)	
IOELV TWA mg/m ³ (UE)	241 mg/m ³
IOELV TWA ppm (UE)	50 ppm
IOELV STEL mg/m ³ (UE)	723 mg/m ³
IOELV STEL ppm (UE)	150 ppm
ethyl acetate (141-78-6)	
IOELV TWA mg/m ³ (UE)	734 mg/m ³
IOELV TWA ppm (UE)	200 ppm
IOELV STEL mg/m ³ (UE)	1468 mg/m ³
IOELV STEL ppm (UE)	400 ppm

DNEL / PNEC

reaction mass of ethylbenzene and xylene			
Type	Value	User	Effect
DNEL long-term inhalative	221 mg/m ³	Workers	Systemic
DNEL long-term dermal	212 mg/kg bw/day	Workers	Systemic
PNEC aquatic, freshwater	0,327 mg/l		
PNEC aquatic, marine water	0,327 mg/l		
PNEC sediment, freshwater	12,46 mg/kg		
PNEC sediment, marine water	12,46 mg/kg		
PNEC soil	2,31 mg/kg		
PNEC sewage treatment plant (STP)	6,58 mg/l		

n-butyl acetate (123-86-4)			
Type	Value	User	Effect
DNEL acute inhalative	600 mg/m ³	Workers	Local
DNEL acute inhalative	600 mg/m ³	Workers	Systemic
DNEL long-term inhalative	300 mg/m ³	Workers	Local
DNEL long-term inhalative	48 mg/m ³	Workers	Systemic
DNEL acute dermal, short-term	11 mg/kg	Workers	Systemic
DNEL long-term dermal	7 mg/kg bw/day	Workers	Systemic
PNEC aquatic, freshwater	0,18 mg/l		
PNEC aquatic, marine water	0,018 mg/l		
PNEC sediment, freshwater	0,981 mg/kg		
PNEC sediment, marine water	0,098 mg/kg		
PNEC soil	0,09 mg/kg		
PNEC sewage treatment plant (STP)	35,6 mg/l		

ethyl acetate (141-78-6)			
Type	Value	User	Effect
DNEL acute inhalative	1468 mg/m ³	Workers	Local
DNEL acute inhalative	1468 mg/m ³	Workers	Systemic
DNEL long-term inhalative	734 mg/m ³	Workers	Local
DNEL long-term inhalative	734 mg/m ³	Workers	Systemic
DNEL long-term dermal	63 mg/kg bw/day	Workers	Systemic
PNEC aquatic, freshwater	0,24 mg/l		
PNEC aquatic, marine water	0,024 mg/l		
PNEC sediment, freshwater	1,15 mg/kg		
PNEC sediment, marine water	0,115 mg/kg		
PNEC soil	0,148 mg/kg		
PNEC sewage treatment plant (STP)	650 mg/l		

n-butyl methacrylate (97-88-1)			
Type	Value	User	Effect
DNEL long-term inhalative	66,5 mg/m ³	Consumers	Systemic
DNEL long-term inhalative	366,4 mg/m ³	Consumers	Local

Duthoo Touch-Up Spray 1 Component

DNEL long-term inhalative	409 mg/m ³	Workers	Local
DNEL long-term inhalative	415,9 mg/m ³	Workers	Systemic
DNEL long-term dermal	5 mg/kg bw/day	Workers	Systemic
DNEL long-term dermal	3 mg/kg bw/day	Consumers	Systemic

8.2 - Exposure controls

Appropriate engineering controls

- If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

- Suitable protective clothing: lab coat

- Protective gloves



SECTION 9: Physical and chemical properties

9.1 - Information on basic physical and chemical properties

<u>Physical state</u>	<u>gaseous</u>	<u>Appearance</u>	<u>Aerosol</u>
<u>Colour</u>	<u>characteristic</u>	<u>Odour</u>	<u>characteristic</u>
Odour threshold		No data available	
pH		No data available	
Melting point		No data available	
Freezing point		No data available	
Boiling point		No data available	
Flash point		No data available	
Evaporation rate		Trager dan ether	
flammability		No data available	
Lower explosion limit		2,6 % Vol.	
Upper explosion limit		26,2 % Vol.	
Vapour pressure		No data available	
Vapour density		No data available	
Relative density		No data available	
Density		0,75 kg/l < V < 0,85 kg/l	
Solubility (Water)		No data available	
Solubility (Ethanol)		No data available	
Solubility (Acetone)		No data available	
Solubility (Organic solvents)		No data available	
Log KOC		No data available	
Auto-ignition temperature		240 °C	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

Particle characteristics

Duthoo Touch-Up Spray 1 Component

Particle size	No data available
Dustiness	No data available
Specific surface area	No data available
Shape	No data available

9.2 - Other information

VOC content	< 840 g/l
Minimum ignition energy	No data available
Conductivity	No data available

SECTION 10: Stability and reactivity

10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.

10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

10.4 - Conditions to avoid

- In case of warming: Ignition hazard
- Do not expose to temperatures exceeding 50 °C/122 °F.
- In case of warming: Danger of bursting container.

10.5 - Incompatible materials

- No information available.

10.6 - Hazardous decomposition products

- No information available.

SECTION 11: Toxicological information

11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Not classified

Toxicity : Mixture

LD50 oral (rat)	No data available
LD50 dermal (rat)	No data available
LD50 dermal (rabbit)	No data available
LC50 inhalation (rat)	No data available
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

Toxicity : Substances

Duthoo Touch-Up Spray 1 Component

reaction mass of ethylbenzene and xylene ()	
LD50 oral (rat)	3523 mg/kg < V < 4000 mg/kg
LD50 dermal (rabbit)	121236 mg/kg
LC50 inhalation vapours (rat)	6350 mg/l < V < 6700 mg/l
acetone, propan-2-one, propanone (67-64-1)	
LD50 oral (rat)	5800 mg/kg
LD50 dermal (rabbit)	> 15800 mg/kg
LC50 inhalation dusts and mists (rat)	76 mg/l
n-butyl acetate (123-86-4)	
LD50 oral (rat)	10768 mg/kg
LD50 dermal (rat)	> 17600 mg/kg
LC50 inhalation vapours (rat)	21,1 mg/l
ethyl acetate (141-78-6)	
LD50 oral (rat)	5620 mg/kg
LD50 dermal (rabbit)	20001 mg/kg
LC50 inhalation vapours (rat)	22,6 mg/l
n-butyl methacrylate (97-88-1)	
LD50 oral (rat)	16000 mg/kg
LD50 dermal (rat)	17900 mg/kg
LC50 inhalation vapours (rat)	29 mg/l

<u>Skin corrosion/irritation</u>	- Not classified
<u>Serious eye damage/eye irritation</u>	- Eye irritation - Category 2 - Causes serious eye irritation
	- Irritating to eyes.
<u>Respiratory or skin sensitisation</u>	- Not classified
<u>Germ cell mutagenicity</u>	- Not classified
<u>Carcinogenicity</u>	- Not classified
<u>Reproductive toxicity</u>	- Not classified
<u>STOT-single exposure</u>	- STOT-single exposure - Category 3 (H336) - May cause drowsiness or dizziness
<u>STOT-repeated exposure</u>	- Not classified
<u>Aspiration hazard</u>	- Not classified

11.2 - Information on other hazards

SECTION 12: Ecological information

12.1 - Toxicity

Toxicity : Mixture

EC50 48 hr crustacea	No data available
LC50 96 hr fish	No data available

Duthoo Touch-Up Spray 1 Component

ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

Toxicity : Substances

reaction mass of ethylbenzene and xylene ()	
LC50 96 hr fish	2,6 mg/l
ErC50 algae	2,2 mg/l
acetone, propan-2-one, propanone (67-64-1)	
LC50 96 hr fish	8300 mg/l
ErC50 algae	7200 mg/l
n-butyl acetate (123-86-4)	
LC50 96 hr fish	100 mg/l
ethyl acetate (141-78-6)	
EC50 48 hr crustacea	750 mg/l
LC50 96 hr fish	212,5 mg/l
ErC50 algae	2500 mg/l
NOEC chronic fish	75,6 mg/l
n-butyl methacrylate (97-88-1)	
NOEC chronic crustacea	2,6 mg/l

- The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.

12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available

- No indication of bioaccumulation potential.

12.4 - Mobility in soil

- No information available.

12.5 - Results of PBT and vPvB assessment

12.6 - Endocrine disrupting properties

12.7 - Other adverse effects

- No information available.

Duthoo Touch-Up Spray 1 Component

SECTION 13: Disposal considerations

13.1 - Waste treatment methods

Waste treatment methods : - Dispose of waste according to applicable legislation.

Sewage disposal : - No information available.

Special precautions for waste treatment : - No information available.

Community or national or regional provisions : - No information available.

SECTION 14: Transport information

14.1 - UN number or ID number

UN number (ADR) : UN1950

UN number (RID) : UN1950

UN number (ADN) : UN1950

UN number (IMDG) : UN1950

UN number (IATA) : UN1950

14.2 - UN proper shipping name

UN proper shipping name (ADR) : AEROSOLS

UN proper shipping name (RID) : AEROSOLS

UN proper shipping name (ADN) : AEROSOLS

UN proper shipping name (IMDG) : AEROSOLS

UN proper shipping name (IATA) : AEROSOLS, FLAMMABLE

14.3 - Transport hazard class(es)

ADR Transport hazard class(es) : 2

ADR Classification code: : 5F

Pictograms



Transport hazard class(es) (RID) : 2

Pictograms



Transport hazard class(es) (ADN) : 2

Duthoo Touch-Up Spray 1 Component

Pictograms



Transport hazard class(es) (IMDG) : 2

Pictograms



Transport hazard class(es) (IATA) : 2

Pictograms



14.4 - Packing group

Packing group :
Packing group (RID) :
Packing group (ADN) :
Packing group (IMDG) :
Packing group (IATA) :

14.5 - Environmental hazards

Environmental hazards : No
Marine pollutant : No

14.6 - Special precautions for user

Duthoo Touch-Up Spray 1 Component

ADR

<u>ADR Classification code:</u>	:	5F
<u>ADR Special provisions</u>	:	190+327+344+625
<u>ADR Limited quantity (LQ)</u>	:	1L
<u>ADR Excepted quantities</u>	:	E0
<u>ADR Packing instructions</u>	:	P207 LP200
<u>ADR Special packing provisions</u>	:	PP87 RR6 L2
<u>ADR Mixed packing provisions</u>	:	MP9
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>ADR tank code</u>	:	
<u>ADR tanks special provisions</u>	:	
<u>Vehicle for tank carriage</u>	:	
<u>ADR Transport category</u>	:	2
<u>ADR Tunnel restriction code</u>	:	D
<u>ADR Special provisions loading, unloading and handling</u>	:	CV9 CV12
<u>Special provisions - Packages</u>	:	V14
<u>Special provisions - Bulk</u>	:	
<u>Special provisions - Operation</u>	:	S2
<u>ADR Hazard identification number (Kemler No.)</u>	:	

RID

<u>Special provisions</u>	:	
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	

ADN

<u>Special provisions</u>	:	
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	

IMDG

<u>Special provisions</u>	:	63 190 277 327 344 381 959
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	E0
<u>Packing instructions</u>	:	P207 LP200
<u>Special packing provisions</u>	:	PP87 L2
<u>IBC instruction(s)</u>	:	
<u>IBC provisions</u>	:	
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>EmS codes</u>	:	F-D, S-U
<u>Stowage and handling</u>	:	Category None SW1 SW22
<u>Segregation</u>	:	SG69
<u>Properties and observations</u>	:	

Duthoo Touch-Up Spray 1 Component

IATA

PCA - Excepted quantities	:	E0
PCA - Limited Quantity - Packing Instructions	:	Y203
PCA - Limited Quantity - Maximum Net Quantity per Package	:	30kg
PCA - Packing Instructions	:	203
PCA - Maximum Net Quantity per Package	:	75kg
CAO - Packing Instructions	:	203
CAO - Maximum Net Quantity per Package	:	150kg
Special Provisions	:	A145 A167 A802
ERG Code	:	10L

14.7 - Maritime transport in bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

Substances REACH candidates None

Substances Annex XIV None

Substances Annex XVII None

VOC content < 840 g/l

15.2 - Chemical Safety Assessment

Chemical safety assessment carried out for the product - No information available.

SECTION 16: Other information

SDS versions

Version	Issue date	Author	Description of the amendments
1,01	18/12/2023		
1	27/11/2023		

Texts of the regulatory sentences

Acute Tox. 4 Dermal	Acute toxicity (dermal) - Category 4
Acute Tox. 4 Inhalation	Acute toxicity (inhalative) - Category 4
Aerosol 1	Aerosol - Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Aquatic Chronic 3
Asp. Tox. 1	Aspiration hazard - Category 1
Eye Irrit. 2	Eye irritation - Category 2
Eye Irrit. 2A	Eye irritation - Category 2A
Flam. Gas 1	Flammable gas. - Category 1
Flam. Liq. 2	Flammable liquid and vapour. - Category 2
Flam. Liq. 3	Flammable liquid and vapour. - Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol

Duthoo Touch-Up Spray 1 Component

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects
Press. Gas	Gases under pressure
Press. Gas (Liq.)	Liquefied gas
Skin Irrit. 2	Irritation, Category 2
Skin Sens. 1	Skin sensitization - Category 1
STOT RE 2	STOT-repeated exposure - Category 2
STOT SE 3 (H335)	STOT-single exposure - Category 3 (H335)
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)

*** **