

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name:** HAKU GB 885  
**Article number:** 400008850000  
**UFI:** 9QT5-R0M4-K00N-GUXA

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Product categories [PC]:** PC9a - Coatings and paints, thinners, paint removers  
PC35 - Washing and cleaning products (including solvent based products)  
**Sector of uses [SU]:** SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites  
**Process categories [PROC]:** PROC7 - Industrial spraying  
PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities  
PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC10 - Roller application or brushing  
PROC11 - Non industrial spraying  
PROC13 - Treatment of articles by dipping and pouring  
PROC19 - Hand-mixing with intimate contact and only PPE available  
PROC28 - Manual maintenance (cleaning and repair) of machinery  
**Environmental release categories [ERC]:** ERC2 - Formulation of preparations (mixtures)  
ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

### 1.3. Details of the supplier of the safety data sheet

**Supplier:** Kluthe Benelux B.V.  
Produktieweg 8  
NL-2404 Alphen aan den Rijn  
Telefon: +31 172/ 516 000  
Telefax: +31 172/ 439 494  
www.kluthe.com  
**E-mail address** sds.nl@kluthe.com

### 1.4. Emergency telephone number

**Emergency Telephone:** +44 20 3885 0382 (CHEMTREC, 24h/7/365; CCN: 1012799)  
CHEMTREC local:  
DE: 0800 1817059 AT: +43 1 3649237 CH: +41 435081970  
NL: +31 85 888 0596 BE: +32 2 808 32 37 FR: +33 9 75 18 14 07  
ES: +34 931768511 PT: +351 308 801 773 IT: +39 02 4555 7031  
DK: +45 69 91 85 73 SE: +46 8 525 034 03 FI: +358 9 42419014  
PL: +48 22 398 80 29 CZ: +420 228 880 039 SK: +421 2/330 579 72  
SI: +386 1 888 80 16 HU: +36 1 808 8425 RO: +40 376 300 026  
UK: +44 20 3807 3798

Emergency Telephone - §45 - (EC)1272/2008	
Austria	+43 1 406 43 43 (Giftinformationszentrale)
Bulgaria	+359 2 9154 213 (Pirogov)
Italy	Centro Antiveleni di Milano: 02.66101029; Centro Antiveleni di Roma: 06.3054343;

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

	Centro Antiveleni di Roma: 06.49978000; Centro Antiveleni di Roma: 06.68593726; Centro Antiveleni di Pavia: 0382.24444; Centro Antiveleni di Firenze: 055.7947819; Centro Antiveleni di Bergamo: 800.883300; Centro Antiveleni di Foggia: 0881.732326; Centro Antiveleni di Napoli: 081.7472870; Centro Antiveleni di Verona: 800.011.858
Slovakia	+421 2 5477 4166 (NTIC)
Hungary	+36 80 201 199; +36 1 476 6464 (ETTSZ)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flammable liquids	Category 2 - (H225)
Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336) Narcotic effects
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Chronic aquatic toxicity	Category 3 - (H412)

### 2.2. Label elements



Signal word: **Danger**

#### Hazard components for labeling:

Contains Toluene, Ethyl acetate, n-Butyl acetate

#### Hazard statements:

H225 - Highly flammable liquid and vapor.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H361d - Suspected of damaging the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

#### EU Specific Hazard Statements:

#### Precautionary Statements - EU (§28, 1272/2008):

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P331 - Do NOT induce vomiting

P370 + P378 - In case of fire: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam to extinguish

## 2.3. Other hazards

**PBT & vPvB:** This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information:** No information available

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	CAS No	EC No (EU Index No)	REACH registration number	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Weight-%
Toluene	108-88-3	203-625-9	01-2119471310-51	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373) Aquatic Chronic 3 (H412)	25 - < 50
Ethyl acetate	141-78-6	205-500-4	01-2119475103-46	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336) (EUH066)	25 - < 50
n-Butyl acetate	123-86-4	204-658-1	01-2119485493-29	Flam. Liq. 3 (H226) STOT SE 3 (H336) (EUH066)	25 - < 50

#### Acute Toxicity Estimate:

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE<sub>mix</sub>) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Toluene 108-88-3	5580	12124	28	No data available	No data available
Ethyl acetate 141-78-6	4934	20000	No data available	14.4131	No data available
n-Butyl acetate 123-86-4	10768	17060	0.74	23.4	No data available

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Full text of H- and EUH-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

General advice:	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation:	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion:	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider:	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians:	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------	---

## SECTION 5: Firefighting measures

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

## 5.1. Extinguishing media

Suitable Extinguishing Media: Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

Large Fire: CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media: Do not scatter spilled material with high pressure water streams.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical: Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## 5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters: Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information: Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders: Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

Environmental precautions: Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

### 6.3. Methods and material for containment and cleaning up

Methods for containment: Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up: Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards: Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Reference to other sections: See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling



Advice on safe handling:

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations:

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions:

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

### 7.3. Specific end use(s)

Other information:

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Exposure Limits:

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> STEL 100 ppm STEL 380 mg/m <sup>3</sup>	TWA: 20 ppm TWA: 77 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>	STEL: 100 ppm STEL: 384.0 mg/m <sup>3</sup> TWA: 50 ppm TWA: 192.0 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

		H*	D*	K*	*
Ethyl acetate 141-78-6	STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL 400 ppm STEL 1468 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>	STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup> STEL 100 ppm STEL 480 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 238 mg/m <sup>3</sup> STEL: 150 ppm STEL: 712 mg/m <sup>3</sup>	STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup> STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>
<b>Chemical name</b>	<b>Cyprus</b>	<b>Czech Republic</b>	<b>Denmark</b>	<b>Estonia</b>	<b>Finland</b>
Toluene 108-88-3	* STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> TWA: 50 ppm TWA: 192 mg/m <sup>3</sup>	TWA: 200 mg/m <sup>3</sup> Ceiling: 500 mg/m <sup>3</sup> D*	TWA: 25 ppm TWA: 94 mg/m <sup>3</sup> H*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> A*	TWA: 25 ppm TWA: 81 mg/m <sup>3</sup> STEL: 100 ppm STEL: 380 mg/m <sup>3</sup> iho*
Ethyl acetate 141-78-6	STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm	TWA: 700 mg/m <sup>3</sup> Ceiling: 900 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 540 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 500 mg/m <sup>3</sup> STEL: 300 ppm STEL: 1100 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 730 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1470 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm	TWA: 241 mg/m <sup>3</sup> Ceiling: 723 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> STEL: 150 ppm STEL: 725 mg/m <sup>3</sup>
<b>Chemical name</b>	<b>France</b>	<b>Germany TRGS</b>	<b>Germany DFG</b>	<b>Greece</b>	<b>Hungary</b>
Toluene 108-88-3	TWA: 20 ppm TWA: 76.8 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> H*	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> Peak: 100 ppm Peak: 380 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> *	TWA: 190 mg/m <sup>3</sup> STEL: 380 mg/m <sup>3</sup> b*
Ethyl acetate 141-78-6	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 730 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 750 mg/m <sup>3</sup> Peak: 400 ppm Peak: 1500 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>	TWA: 734 mg/m <sup>3</sup> STEL: 1468 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup> STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>	TWA: 62 ppm TWA: 300 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 480 mg/m <sup>3</sup> Peak: 200 ppm Peak: 960 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup> STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> STEL: 723 mg/m <sup>3</sup>
<b>Chemical name</b>	<b>Ireland</b>	<b>Italy MDLPS</b>	<b>Italy AIDII</b>	<b>Latvia</b>	<b>Lithuania</b>
Toluene 108-88-3	TWA: 192 mg/m <sup>3</sup> TWA: 50 ppm STEL: 384 mg/m <sup>3</sup> STEL: 100 ppm Sk*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> cute*	TWA: 20 ppm TWA: 75.4 mg/m <sup>3</sup>	TWA: 14 ppm TWA: 50 mg/m <sup>3</sup> STEL: 40 ppm STEL: 150 mg/m <sup>3</sup> Ada*	O* TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup>
Ethyl acetate 141-78-6	TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	TWA: 400 ppm TWA: 1441 mg/m <sup>3</sup>	TWA: 200 mg/m <sup>3</sup> TWA: 54 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	TWA: 150 ppm TWA: 500 mg/m <sup>3</sup> Ceiling: 300 ppm Ceiling: 1100 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm	TWA: 50 ppm TWA: 238 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm	TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm
<b>Chemical name</b>	<b>Luxembourg</b>	<b>Malta</b>	<b>Netherlands</b>	<b>Norway</b>	<b>Poland</b>
Toluene 108-88-3	Peau* STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> TWA: 50 ppm TWA: 192 mg/m <sup>3</sup>	skin* STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> TWA: 50 ppm TWA: 192 mg/m <sup>3</sup>	TWA: 150 mg/m <sup>3</sup> STEL: 384 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 94 mg/m <sup>3</sup> STEL: 37.5 ppm STEL: 141 mg/m <sup>3</sup> H*	STEL: 200 mg/m <sup>3</sup> TWA: 100 mg/m <sup>3</sup> skóra*
Ethyl acetate 141-78-6	STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup> TWA: 200 ppm TWA: 734 mg/m <sup>3</sup>	TWA: 734 mg/m <sup>3</sup> STEL: 1468 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>	STEL: 1468 mg/m <sup>3</sup> TWA: 734 mg/m <sup>3</sup>

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

n-Butyl acetate 123-86-4		STEL: 150 ppm STEL: 723 mg/m <sup>3</sup> TWA: 50 ppm TWA: 214 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> STEL: 723 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm STEL: 723 mg/m <sup>3</sup> STEL: 150 ppm	STEL: 720 mg/m <sup>3</sup> TWA: 240 mg/m <sup>3</sup>
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Cutânea*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> P*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> K* Ceiling: 384 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> K*	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> via dérmica*
Ethyl acetate 141-78-6	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	TWA: 111 ppm TWA: 400 mg/m <sup>3</sup> STEL: 139 ppm STEL: 500 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> Ceiling: 1100 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 734 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1468 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup> STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 715 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 500 mg/m <sup>3</sup> Ceiling: 700 mg/m <sup>3</sup>	TWA: 241 mg/m <sup>3</sup> TWA: 50 ppm STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 241 mg/m <sup>3</sup> STEL: 150 ppm STEL: 723 mg/m <sup>3</sup>
Chemical name	Sweden	Switzerland	United Kingdom	Russia	Turkey
Toluene 108-88-3	NGV: 50 ppm NGV: 192 mg/m <sup>3</sup> Bindande KGV: 100 ppm Bindande KGV: 384 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 190 mg/m <sup>3</sup> STEL: 200 ppm STEL: 760 mg/m <sup>3</sup> H*	TWA: 50 ppm TWA: 191 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*	TWA: 50 mg/m <sup>3</sup> MAC: 150 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> S*
Ethyl acetate 141-78-6	NGV: 150 ppm NGV: 550 mg/m <sup>3</sup> Bindande KGV: 300 ppm Bindande KGV: 1100 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 730 mg/m <sup>3</sup> STEL: 400 ppm STEL: 1460 mg/m <sup>3</sup>	TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	TWA: 50 mg/m <sup>3</sup> MAC: 200 mg/m <sup>3</sup>	
n-Butyl acetate 123-86-4	NGV: 50 ppm NGV: 241 mg/m <sup>3</sup> Bindande KGV: 150 ppm Bindande KGV: 723 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> STEL: 150 ppm STEL: 720 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 724 mg/m <sup>3</sup> STEL: 200 ppm STEL: 966 mg/m <sup>3</sup>	TWA: 50 mg/m <sup>3</sup> MAC: 200 mg/m <sup>3</sup>	

Biological occupational exposure limits:

Chemical name	European Union	Germany DFG	Netherlands	Spain	United Kingdom	Hungary
Toluene 108-88-3	-	600 µg/L (whole blood - Toluene immediately after exposure) 75 µg/L (urine - Toluene end of shift) 1.5 mg/L (urine - o-Cresol (after hydrolysis) for long-term exposures: at the end of the shift after several shifts) 1.5 mg/L (urine - o-Cresol (after hydrolysis) end of shift)		0.6 mg/L - urine (o-Cresol) - end of shift 0.05 mg/L - blood (Toluene) - start of last shift of workweek 0.08 mg/L - urine (Toluene) - end of shift	-	1 mg/g Creatinine (urine - o-Cresol end of shift) 1 µmol/mmol Creatinine (urine - o-Cresol end of shift)



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Chemical name	European Union	Germany DFG	Netherlands	Spain	United Kingdom	Hungary
		600 µg/L - BAT (immediately after exposure) blood 75 µg/L - BAT (end of exposure or end of shift) urine 1.5 mg/L - BAT (for long-term exposures: at the end of the shift after several shifts) urine 1.5 mg/L - BAT (end of exposure or end of shift) urine				

Chemical name	France	Italy MDLPS	Portugal	Finland	Denmark	Czech Republic
Toluene 108-88-3	1 mg/L - venous blood (Toluene) - end of shift 2500 mg/g creatinine - urine (Hippuric acid) - end of shift	-	-	500 nmol/L - blood (Toluene) - in the morning after a working day		

Chemical name	Austria	Switzerland	Poland	Norway	Ireland	Russia
Toluene 108-88-3	10 g/dL Hemoglobin (blood - by the first screening and once yearly) 12 g/dL Hemoglobin (blood - by the first screening and once yearly) 3.2 million/µL Erythrocytes (blood - by the first screening and once yearly) 3.8 million/µL Erythrocytes (blood - by the first screening and once yearly) 4000 Leukocytes/µL (blood - by the first screening and once yearly) 13000 Leukocytes/µL (blood - by the first screening and once yearly) 130000 Thrombocytes/µL	600 µg/L - whole blood (Toluene) - end of shift 6.48 µmol/L - whole blood (Toluene) - end of shift 2 g/g creatinine - urine (Hippuric acid) - end of shift, and after several shifts (for long-term exposures) 1.26 mmol/mmol creatinine - urine (Hippuric acid) - end of shift, and after several shifts (for long-term exposures) 0.5 mg/L - urine (o-Cresol) - end of shift, and after several shifts (for long-term exposures) 4.62 µmol/L - urine (o-Cresol) - end of shift, and after several shifts (for long-term exposures)	-	-	0.02 mg/L (blood - Toluene prior to last shift of workweek) 0.03 mg/L (urine - Toluene end of shift) 0.3 mg/g Creatinine (urine - o-Cresol end of shift)	

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Revision Number: 1

Print Date: 13-Apr-2024

HAKU GB 885 - 400008850000

Chemical name	Austria	Switzerland	Poland	Norway	Ireland	Russia
	(blood - by the first screening and once yearly) 150000 Thrombocytes/ $\mu$ L (blood - by the first screening and once yearly) 0.8 mg/L (urine - o-Cresol after end of work day, at the end of a work week/end of the shift)	75 $\mu$ g/L - urine (Toluol) - end of shift				

Derived No Effect Level (DNEL):

component information:

Worker - inhalative:

Chemical name	long-term, systemic	short-term, systemic	long-term, local	short-term, local
Toluene	192 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>
Ethyl acetate	734 mg/m <sup>3</sup>	1468 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	1468 mg/m <sup>3</sup>

Worker - dermal:

Chemical name	long-term, systemic	short-term, systemic	long-term, local	short-term, local
Toluene	384 mg/kg bw/day			
Ethyl acetate	63 mg/kg bw/day			

Consumer - inhalative:

Chemical name	long-term, systemic	short-term, systemic	long-term, local	short-term, local
Toluene	56.5 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>	56.5 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>
Ethyl acetate	367 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	367 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>

Consumer - dermal:

Chemical name	long-term, systemic	short-term, systemic	long-term, local	short-term, local
Toluene	226 mg/kg bw/day			
Ethyl acetate	37 mg/kg bw/day			

Consumer - oral:

Chemical name	long-term, systemic	short-term, systemic	long-term, local	short-term, local
Toluene	8.13 mg/kg bw/day			
Ethyl acetate	4.5 mg/kg bw/day			

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Predicted No Effect Concentration (PNEC):

component information:

Chemical name	Toluene CAS: 108-88-3
Freshwater	0.68 mg/L
Marine water	0.68 mg/L
Freshwater (intermittent release)	0.68 mg/L
Sewage treatment	13.61 mg/L
Freshwater sediment	16.39 mg/kg sediment dw
Marine sediment	16.39 mg/kg sediment dw
Soil	2.89 mg/kg soil dw
Chemical name	Ethyl acetate CAS: 141-78-6
Freshwater	0.24 mg/L
Marine water	0.024 mg/L
Freshwater (intermittent release)	1.65 mg/L
Sewage treatment	650 mg/L
Freshwater sediment	1.15 mg/kg sediment dw
Marine sediment	0.115 mg/kg sediment dw
Soil	0.148 mg/kg soil dw
Food chain	0.2 g/kg food
Chemical name	n-Butyl acetate CAS: 123-86-4
Freshwater	0.18 mg/L
Marine water	0.018 mg/L
Freshwater (intermittent release)	0.36 mg/L
Sewage treatment	35.6 mg/L
Freshwater sediment	0.981 mg/kg sediment dw
Marine sediment	0.0981 mg/kg sediment dw
Soil	0.0903 mg/kg soil dw

## 8.2. Exposure controls

Engineering controls:

Showers, eyewash stations, and ventilation systems.

Personal protective equipment:

The usual precautionary measures for the handling of chemicals have to be observed.



Eye/face protection:

Tight sealing safety goggles.

Hand protection:

Wear suitable gloves. Impervious gloves.

PPE - Glove material	Glove thickness	Break through time
PVA (Polyvinyl alcohol)	0.7 mm	>=480 min.

Skin and body protection:

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Respiratory protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Recommended Filter Type: Filtering device (full mask or mouthpiec) with filter: AP-2

Environmental exposure controls: No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid				
Color	colorless				
Odor	characteristic				
			Conditions	Method	Remarks
Melting point / melting range					Not established
Boiling point / boiling range	75 - 135	°C			
Flammability					Not established
Decomposition temperature					not relevant
Flash point	~ 3.2	°C			
Autoignition temperature	260	°C			
Lower explosive limit	1.4	Vol%			
Upper explosion limit	8.1	Vol%			
Vapor pressure	4.48	kPa	20 °C		
Density	0.862 - 0.872	g/cm <sup>3</sup>	20 °C		Not applicable
Water solubility	~ 1.7	%			
pH					Not applicable
pH (as aqueous solution)					Not established
Partition coefficient					Not established
Kinematic viscosity					Not applicable
Odor threshold					Not established
Relative density					Not established
Evaporation rate					Not established
Relative vapor density	no data available				
Particle Size	no data available				
Particle Size Distribution	no data available				

### 9.2. Other information

Bulk density: no data available

Softening point: No information available

Molecular weight: No information available

#### 9.2.1. Information with regard to physical hazard classes:

Explosive properties: No data available

Oxidizing properties: No data available

#### 9.2.2. Other safety characteristics: No information available

## SECTION 10: Stability and reactivity

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

## 10.1. Reactivity

Reactivity: No information available.

## 10.2. Chemical stability

Stability: Stable under normal conditions.

Explosion data:

Sensitivity to mechanical impact: None.

Sensitivity to static discharge: Yes.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions: None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid: Heat, flames and sparks.

## 10.5. Incompatible materials

Incompatible materials: Strong acids. Strong bases. Strong oxidizing agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products: None known based on information supplied.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure:

Product Information:

Inhalation: Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact: Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact: Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion: Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

## Symptoms related to the physical, chemical and toxicological characteristics:

Symptoms: Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Numerical measures of toxicity:

Acute toxicity: The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral): 19,243.10 mg/kg

ATEmix (inhalation-vapor): 69.40 mg/l

Component Information:

Chemical name	Parameter	Species	Effective dose	Method
Toluene 108-88-3	Oral LD50	Rat	5580 mg/kg	OECD 401
Ethyl acetate 141-78-6	Oral LD50	Rabbit Rat	4934 mg/kg	OECD 401
n-Butyl acetate 123-86-4	Oral LD50	Rat	10768 mg/kg	OECD 423

Chemical name	Parameters	Species	Effective dose	Method
Toluene 108-88-3	Dermal LD50	Rabbit	> 5000 mg/kg	
Ethyl acetate 141-78-6	Dermal LD50	Rabbit	> 20000 mg/kg	
n-Butyl acetate 123-86-4	Dermal LD50	Rabbit	> 5000 mg/kg	OECD 402

Chemical name	Parameters	Species	Effective dose	Exposure time	Method
Toluene 108-88-3	Inhalation LC50	Rat	28.1 mg/L	4 h	OECD 403
Ethyl acetate 141-78-6	Inhalation LC50	Rat	> 6000 ppm	6 h	
n-Butyl acetate 123-86-4	Inhalation LC50	Rat	23.4 mg/m <sup>3</sup>	4 h	OECD 403

## Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Skin corrosion/irritation:	Causes skin irritation.
Serious eye damage/eye irritation:	Causes serious eye irritation.
Respiratory or skin sensitization:	No information available.
Germ cell mutagenicity:	No information available.
Carcinogenicity:	No information available.
Reproductive toxicity:	Contains a known or suspected reproductive toxin. Classification based on data available for ingredients.

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Suspected of damaging fertility or the unborn child.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Toluene	Repr. 2

STOT - single exposure:

May cause drowsiness or dizziness.

STOT - repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Chemical name	Exposure route	Target Organs
Toluene 108-88-3	Inhalation	nervous system

Aspiration hazard:

May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

No information available.

### 11.2.2. Other information

No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecotoxicity: Harmful to aquatic life with long lasting effects.

fish toxicity:

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
Toluene 108-88-3	LC50 NOEC	Oncorhynchus kisutch	5.5 mg/L 1.39 mg/L	96 h 40 d	
Ethyl acetate 141-78-6	LC50 NOEC	Pimephales promelas	220 - 250 mg/L > 9.65 mg/L	96 h 32 d	
n-Butyl acetate 123-86-4	LC50	Pimephales promelas	17 - 19 mg/L	96 h	OECD 203

toxicity to crustacea:

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
Toluene	EC50	Cerodaphnia	3.23 mg/L	48 h	

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Revision Number: 1

Print Date: 13-Apr-2024

HAKU GB 885 - 400008850000

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
108-88-3		dubia			
Ethyl acetate 141-78-6	EC50	Daphnia magna	560 mg/L 2.4 mg/L	48 h 21 d	- OECD 211
n-Butyl acetate 123-86-4	EC50	Daphnia magna	44 mg/L	48 h	OECD 202

Algae Toxicity:

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
Toluene 108-88-3	EC50	Chlorella vulgaris	134 mg/L	72 h	
Ethyl acetate 141-78-6	EC50	Desmodesmus subspicatus	5600 mg/L > 100 mg/L	48 h 72 h	DIN 38412 OECD 201
n-Butyl acetate 123-86-4	EC50	Desmodesmus subspicatus	674.7 mg/L	72 h	

Bacteria toxicity:

Chemical name	Parameters	Species	Effective dose	Exposure time	Method
Ethyl acetate 141-78-6	EC 50	Photobacterium phosphoreum	5870 mg/L	15 min.	OECD 201

## 12.2. Persistence and degradability

Persistence and degradability:

Chemical name	degradation rate	test duration	Rapidly biodegradable	Remarks	Method
Toluene 108-88-3	81 %	5 d	Yes		
Ethyl acetate 141-78-6	79 %	20 d	Yes		OECD 301 D
n-Butyl acetate 123-86-4	23 %	28 d	Yes		

## 12.3. Bioaccumulative potential

Bioaccumulation:

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Toluene 108-88-3	2.73	90
Ethyl acetate 141-78-6	0.73	30
n-Butyl acetate 123-86-4	2.3	15

## 12.4. Mobility in soil



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Mobility in soil: No information available.

Mobility: No information available.

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment: No information available

Chemical name	PBT and vPvB assessment
Toluene 108-88-3	The substance is not PBT / vPvB
Ethyl acetate 141-78-6	The substance is not PBT / vPvB
n-Butyl acetate 123-86-4	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties.

No information available.

## 12.7. Other adverse effects.

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products: Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging: Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Waste codes / waste designations according to EWC / AVV: 14 06 03\* (other solvents and solvent mixtures)

## SECTION 14: Transport information

### 14.1. UN number

ADR: UN1263  
RID: UN1263  
IMDG: UN1263  
IATA: UN1263

### 14.2 UN proper shipping name

ADR: PAINT RELATED MATERIAL  
UN1263, PAINT RELATED MATERIAL, 3, II

RID: PAINT RELATED MATERIAL  
UN1263, PAINT RELATED MATERIAL, 3, II

PAINT RELATED MATERIAL

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

---

IMDG:

UN1263, PAINT RELATED MATERIAL, 3, II, (3.22°C C.C.)

IATA:

PAINT RELATED MATERIAL

UN1263, PAINT RELATED MATERIAL, 3, II

## 14.3. Transport hazard class(es)

ADR:

3

Hazard label(s)

3

Classification code

F1

ADR Hazard Id (Kemmler

33

Number)

Tunnel restriction code

(D/E)

Limited quantity (LQ)

5 L

Excepted quantity

E2

RID:

3

Labels

3

Classification code

F1

IMDG:

3

Hazard label(s)

3

Limited quantity (LQ)

5 L

Excepted quantity

E2

EmS-No.

F-E, S-E

IATA:

3

Hazard label(s)

3

Excepted quantity

E2

## 14.4. Packing group

ADR:

II

RID:

II

IMDG:

II

IATA:

II

## 14.5. Environmental hazards

ADR:

No

RID:

No

IMDG:

No

IATA:

No

## 14.6. Special precautions for user

ADR:

Special Provisions: 163, 640C, 650, 367

RID:

Special Provisions: 163, 367, 640C, 650

IMDG:

Special Provisions: 163, 367

IATA:

Special Provisions: A3, A72, A192

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

ERG Code

3L

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union:

Regulation (EC) No. 1907/2006 (Annex II - (EC) No. 2020/878) and Regulation (EC) No. 1272/2008

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Take note of Directive 94/33/EC on the protection of young people at work:

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken

Authorizations and/or restrictions on use:

- This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Substance subject to authorization per REACH Annex XIV	Restricted substance per REACH Annex XVII
Toluene 108-88-3		48. 75.
Ethyl acetate 141-78-6		3 40
n-Butyl acetate 123-86-4		3. 40. 75

Persistent Organic Pollutants:  
(EC) 2019/1021

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU):

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009: Not applicable

volatile organic compounds (VOC) content:

acc. reg. 2010/75/EC (20°C):

98.833902199999997 %

acc. reg. 2004/42/EC (Decopaint):

100 %

648/2004/ EU (DetVo):

≥ 30% aromatic hydrocarbons

#### National regulations:

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Denmark:

Chemical name	Denmark - MAL
Toluene 108-88-3	74 m3/10 g substance MAL factor >=10.0 % by weight [3]
Ethyl acetate 141-78-6	13 m3/10 g substance MAL factor >0 % by weight [1]
n-Butyl acetate 123-86-4	14 m3/10 g substance MAL factor >0 % by weight [1]

Germany:

Water hazard class (WGK): strongly hazardous to water (WGK 3) - Classification according to AwSV

Chemical name	WGK Classification (AwSV)	ID number
Toluene 108-88-3	3	194
Ethyl acetate 141-78-6	1	95
n-Butyl acetate 123-86-4	1	42

TA Luft (German Air Pollution Control Regulation):

org. substances (Ziffer 5.2.5):

50 - 55%

org. subst. (digit 5.2.5) class I:

45 - 50%

Storage class (TRGS 510): LGK13 - Non-combustible solids

France:

Occupational Illnesses (R-463-3, France):

Chemical name	French RG number
Toluene 108-88-3	RG 4bis, RG 84
Ethyl acetate 141-78-6	RG 84
n-Butyl acetate 123-86-4	RG 84

RG 4bis - Gastrointestinal conditions caused by benzene, toluene, xylenes, and any products containing them

RG 84 - Conditions caused by occupational use of liquid organic solvents

Netherlands:

Chemical name	Toluene
Netherlands - List of Reproductive Toxins	Development Category 2

Water contaminating class (Netherlands):

C2

Austria:

Flammable Liquids Regulations, VbF

Flammable liquids Cat. 2

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

## Poland:

Ordinance of the Minister of Family, Labor and Social Policy dated June 12, 2018 on the highest permissible concentrations and intensities of harmful factors for health in the work environment (Dz. U. 2018 item 1286, as amended)

Act of December 14, 2012 on waste (Journal of Laws of 2013, item 21; as amended)

Act on chemical substances and their mixtures of February 25, 2011. (Journal of Laws No. 63, item 322; as amended)

Regulation of the Minister of Labor and Social Policy of September 26, 1997 on general regulations of safety and hygiene at work (Dz. U. of 2003, No. 169, item 1650; as amended).

## Switzerland:

VOC content:: acc. VOCV CH 814.018, att. 1: 100 %

## Hungary:

Decree No 44/2000 (XII.27.) of the Ministry of Economic Affairs and Labour of the Republic of Hungary on certain procedures and activities Joint Decree No. 5/2020 ITM on Chemical Safety at Work 178/2017 (VII. 5.)

Government Decree on the European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) „A“ and „B“ of the European Agreement on Road Transport

## **International Inventories:**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

## **Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**NZIoC** - New Zealand Inventory of Chemicals

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

## **15.2. Chemical safety assessment**

Chemical Safety Report: No information available

## **SECTION 16: Other information**

Key or legend to abbreviations and acronyms used in the safety data sheet:

Full text of H-Statements referred to under section 3:

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

---

EUH066 - Repeated exposure may cause skin dryness or cracking  
H225 - Highly flammable liquid and vapor  
H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects

## Legend:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
ADR: European agreement concerning the international carriage of dangerous goods by road  
(Accord européen relatif transport des marchandises dangereuses par route)  
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany)  
BCF: Bio-Concentration Factor  
BOD(5): Biochemical oxygen demand (within 5 days)  
CAS: Chemical Abstract Service  
CLP: Classification, Labelling and Packaging  
CMR: Carcinogenic, Mutagenic, toxic for Reproduction  
DIN: German Standards Institute / German industrial norm  
DNEL: Derived No Effect Level  
DOC: Dissolved organic carbon  
EAK/ AVV: European waste catalogue/ waste directory-regulation  
EC50: Effective Concentration 50%  
ECHA: European Chemical Agency  
EINECS: European Inventory of Existing Commercial Chemical Substances  
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
IATA: International Air Transport Association  
IC50: Inhibition Concentration 50%  
IMDG: International Maritime Dangerous Goods Code  
LC50: Lethal Concentration 50% - LD50: Lethal dose 50%  
MAK: Treshold limit values Germany  
NLP: No Longer Polymers  
NOAEC: No Observed Adverse Effect Concentration  
NOAEL: No Observed Adverse Effect Level  
OECD: Organization for Economic Cooperation and Development  
PBT: persistent, bioaccumulative, toxic  
PC: Product category  
PNEC: Predicted No Effect Concentration  
REACH: Registration, Evaluation and Authorization of Chemicals  
RID: Regulations concerning the international carriage of dangerous goods by rail  
(Règlement International concernant le transport de marchandises dangereuses par chemin de fer)  
STEL: Short-term Exposure Limit  
STP: Sewage treatment plant  
SVHC: Substance of Very High Concern  
TLV: Threshold Limit Value  
TWA: Time Weighted Average  
UN: United Nations  
VOC: Volatile Organic Compounds  
vPvB: very persistent, very bioaccumulative

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision date: 15-Dec-2023

Print Date: 13-Apr-2024

Revision Number: 1

HAKU GB 885 - 400008850000

Ceiling: Maximum limit value

\* Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapor	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitization	Calculation method
Skin sensitization	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS:

European Chemicals Agency (ECHA)

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

Revision date: 07-Jul-2023

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH):

## Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation,

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**Revision date:** 15-Dec-2023

**Print Date:** 13-Apr-2024

**Revision Number:** 1

HAKU GB 885 - 400008850000

---

disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**