

Technical Data Sheet



CLEAR VARNISH SPRAY

CLEARCOAT

- 1 component metal clearcoat with quick drying time in spraycan.
- Available in matt 30% and semi-gloss 70%.

TECHNICAL PROPERTIES

- Direct adhesion on steel, bronze, brass, aluminium,...
- Clean the metal surface with the Duthoo Etching Promotor.
- Yield: 1 m² per spraycan for 20/25µ dry layer thickness.
- Quick drying
- For exterior, UV sensitive and need to be coated with a 1C or 2C clearcoat.
- Dust free after several minutes, when RH is not higher than 70%.
Manageable after 10 min - Completely dry after 2 h.
- Professional use
- Shelf life: 1 year in unopened packaging. Store according to the general requirements for aerosols.
Keep away from frost, humidity and heat.
- Inflammable

USE

- The surfaces must be free of any impurities.
- Pretreatment of non-ferrous metals with the Etching promoter. Ferrous metals and anodization must be sanded with Abranylon and cleaned with the Etching promoter.
- Shake spraycan well before use (2 to 3 minutes). Spray at a distance of 20-25 cm.
- Apply in several thin wet coats until the desired thickness is reached.
- The spraycan contains 2 nozzles: 1 flat jet and 1 round jet.
- Avoid use at temperature below 15 ° c and in extreme heat or humidity.
- To promote the retention time of your spraycan, hold your spraycan upside down and spray until no more paint comes out. Store upside down.

PACKAGING

400 ML SPRAYCAN